

Elite Acoustic-Matt -Technical Data & Specification Sheet

Contact Pristine Coatings on 01492 544777

Product Name: Elite Acoustic-Matt stain covering, solvent based, high opacity coating for interior suspended ceilings. Acoustic Matt has been designed for use on heavy staining and contamination.

Supplier: Pristine Coatings, Unit 10 Phoenix Workshops, Station Rd, Mochdre, Colwyn Bay, LL28 5EF. Tel 01492 544777

Description: Elite Acoustic-Matt is a problem solving stain covering solvent based coating. It is self priming and has been designed to cover heavy staining including nicotine, smoke, fire damage & graffiti without the need to washing down, or priming. Acoustic Matt is without doubt the best stain blocking problem solving solvent based product on the market today. Acoustic-matt offers a 100% matt flat finish.

Where to Use: Suspended ceilings, plasterboard, concrete, plaster, cladding, wood, existing paint films, wallpaper & galvanised.

Properties:

- Excellent stain covering, inc nicotine & water stains
- Solvent based
- Flat matt uniform finish with no roller marks
- Excellent productivity
- Self priming finish coat
- Durability
- washable
- Will not flake or peel
- Vapour permeable

Specification

Preparation: brush down the surface to remove all dust, cobwebs etc, de-grease any heavy contamination, spot prime any bare steel or seal any wet watermarks, mask up if product to be applied by spray.

Application: Acoustic-Matt can be applied by brush, roller or airless spray. For brush and roller application do not dilute, apply a 50 / 50 mist coat then one full coat to finish. Acoustic-Matt should remove the need for a 2nd topcoat

If applied by airless spray use a 0.13 to 0.15 tip, dilute by 5% and apply one full coat overlapping each pass by 50%. This should be sufficient. However depending on the substrate a further mist coat may be required to complete the project.

Completion: Clean brush, roller & machine with warm water, clean area ready for re-occupation.

Tech data:

Colour	White as standard but can be supplied in any RAL or BS colour
Solids	62%
Spread rate	6m ² per litre depending on WFT Required.
Dry to touch	20 minutes
Recoat after	1.5 hours
Clean-up	Spirits
Flash Point	70°C
WFT	between 250 microns
Containers	15 litres

