

Elite Blackout -Technical Data & Specification Sheet

Contact Pristine Coatings on 01492 544777

Product Name: Elite Blackout

Supplier: Pristine Coatings, Unit 10 Phoenix Workshops, Station Rd, Mochdre, Colwyn Bay, LL28 5EF. Tel 01492 544777

Description: Elite Blackout has been formulated for spray application to interior Ceilings, ceiling voids, walls and structural steel. Elite Blackout has been designed to adhere to all substrates commonly found in Ceiling voids. Saving time & money due to one product being used Instead of various ones to achieve a uniform finish.

Where to Use: interior Cladding, concrete, plaster, metal ceilings, HVAC trunking, galvanised steel, PVC, Curtain walls & suspended ceilings.

Properties:

- Ideal for blacking out ceiling voids
- Waterbased
- Self priming
- Excellent productivity
- Excellent adhesion
- Durability
- Minimum Masking (overspray turns to dust)

Specification:

Preparation: Remove any contamination that would effect adhesion
Sand down glossy surfaces to form a key.
Sheet-up accordingly to protect fixtures & fittings.
Treat rust and corrosion prior to spraying.
Brush substrate to remove all dust & cobwebs.

Application:

Do not dilute, product is ready for application by airless spray.
Apply Elite Blackout onto substrate overlapping 50% on each pass.
Use Airless Spray with tip size .013 to .015
Spray onto all substrates contained in ceiling at the same time.

Completion;

On completion leave area for 20 mins to let overspray settle.
Clean & remove all materials & plant from working area.
Remove all masking and rubbish and brush up any overspray.
Inspect the area and leave area ready for re-occupation.

Tech data:

Colour	Black Matt
Solids	40%
Spread rate	10m ² per litre depending on substrate.
Dry to touch	45 minutes
Recoat after	5 hours
Clean-up	Warm Soapy Water
Flash Point	100°C
WFT	150 microns
DFT	50 microns
Containers	20 litres

